

CERTIFICATE OF COMPLIANCE

Certificate Number 20190531-R38578
Report Reference R38578-20151125
Issue Date 2019-MAY-31

Issued to: LAIDLAW GULF LLC
PO BOX 185292
MAYFAIR BUILDING DUBAI INVESTMENT PARK,
PHASE 1 DUBAI AEGB

This certificate confirms that representative samples of FIRE-EXIT HARDWARE
See Addendum Page for Models

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Positive Pressure Fire Tests of Door Assemblies, ANSI/UL 10C

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number 20190531-R38578
Report Reference R38578-20151125
Issue Date 2019-MAY-31

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Rim Type, LG.LAPH.401F.01.153, LG.LAPH.401F.01.154, LG.LAPH.401F.16.150, LG,LAPH.401S.01.153, LG,LAPH.401S.01.154, LG,LAPH.401P.16.150, for use on 1-1/2 Hours single swinging fire doors up to and including 48 in. in width. by 96 in. in height.

Surface-mounted vertical rod type, LG.LAPH.406F.01.153, LG.LAPH.406F.01.154, LG.LAPH.406F.16.150, LG,LAPH.406S.01.153, LG,LAPH.406S.01.154, LG,LAPH.406P.16.150, for use on 1-1/2 Hours single swinging fire doors up to and including 48 in. in width. by 96 in. in height. .



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

